

SpeechMike

Dictation microphone

LFH3200/3300 [Find similar products](#) ▶

- Overview
- Versions
- Specifications
- Support

Connectivity

USB:	High-speed USB 2.0
------	--------------------

Audio recording

Microphone type:	electret condenser microphone
Microphone capsule:	10 mm
Characteristic:	uni-directional
Frequency response:	200–10 000 Hz
Sensitivity:	85 dB–104 dB (depending on position of mic-slider in sound control panel)
Signal-to-noise ratio:	> 70 dBA

Sound

Speaker type:	built-in round, dynamic speaker
Speaker diameter:	30 mm
Acoustic frequency response:	300–7500 Hz
Speaker output power:	> 200 mW

System requirements for Philips SpeechControl software

Processor:	Intel dual core or equivalent AMD processor, 1 GHz or faster processor
RAM:	2 GB (32 bit)/4 GB (64 bit)
Hard-disk space:	30 MB for SpeechControl software, 4.5 GB for Microsoft .NET Framework
Operating system:	Windows 10 (64 bit), Windows 8.1/7 (32/64 bit), Windows Server 2012 (64 bit), Windows Server 2008 R2 (32/64 bit), macOS 10.11/10.12
Graphics:	DirectX-compliant graphics card with hardware acceleration recommended
Sound:	Windows-compatible sound device
Free USB port	
Supported speech recognition software:	Nuance Dragon Professional 12.5/13/14/15 Individual/Group, Nuance Dragon Legal 12.5/13/14/15, Dragon Medical Practice Edition 2/3, Nuance Dragon SDK Client Edition 14

Green specifications

Compliant to 2011/65/EU (RoHS)

Lead-free soldered product

Operation conditions

Temperature:	5 °–45 °C/41 °–113 °F
Humidity:	10 %–90 %

Dimensions

Product dimensions (W × D × H):	45 mm × 165 mm × 30 mm/1.8" × 6.5" × 1.2"
Weight:	0.160 kg/0.353 lb
Cable length:	3 m/10 ft